



CHASE LINK
LICHFIELD ROAD
BROWNHILLS, WALSALL
WEST MIDLANDS
WS8 6LA

Telephone: 01543 360777
Facsimile: 01543 360977

SPECIFICATIONS: 14 CUYD EASY DISCHARGE CONTAINER - LWT (ES/006LW)

CONTAINER SPECIFICATIONS

<u>BASE</u>	4mm mild steel plate (single plate) supported by
<u>BASE SUPPORTS</u>	Twin runners of RSC102mm x 51mm (4" x 2" channel)
<u>SIDES & END</u>	3mm mild steel plate
<u>ROOF</u>	3mm mild steel plate
<u>REINFORCEMENT</u>	RSC76mm x 38mm x 6.7kg/metre
<u>LIFTING LUGS</u>	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	35mm mild steel tipping bar with FLT6mm pressed plate supports – TIPPING END ONLY

DOOR SPECIFICATIONS

<u>TIPPING END</u>	3mm mild steel side opening full width and full height double doors Reinforced with PSC76mm x 38mm formed from 3mm mild steel plate Doors are secured in the closed position using a 35mm locking shaft with 25mm thick profiled locking hooks Locking shafts held closed by secondary retaining bracket secured using a pin and chain assembly
<u>OTHER END</u>	3mm full width double doors with FLT50mm x 5mm slam strip and RND10mm handles Doors are secured in the closed position using a spring bolt on top and bottom of doors And an antiluce fastener (to which a padlock may be fitted by customer)

PAINTING SPECIFICATIONS

<u>INSIDE</u>	Unpainted
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



Showing REL type rear doors



USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD ENCLOSED SKIP PRICES

- (1) **ALL** plate seams fully welded – outside only / inside is stitched
- (2) **FULLY WELD** along top of top channels (to help prevent the ingress of water spoiling paint finish)
- (3) **SKIP LUGS** fitted through channels and side plate (fully welded both inside and outside)
- (8) **ALL SKIPS** of 8 CUYDS and above have backing plates welded behind skip lugs
- (9) **ALL SKIPS** of 8 CUYDS and over have both ends of tipping bar(s) capped in
- (4) **GJF ASSET** numbers welded on all containers for trace ability and security
- (7) **FACILITY** to weld on customer's asset numbers
- (8) **ALL STEEL** used is prime mild HR15 or 43A

OVERALL INTERNAL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
11' 8" (3556mm)	5' 9" (1753mm)	6' (1830mm)