



CHASE LINK
LICHFIELD ROAD
BROWNHILLS, WALSALL
WEST MIDLANDS
WS8 6LA

Telephone: 01543 360777
Facsimile: 01543 360977

SPECIFICATIONS: 14 CUYD EASY DISCHARGE CONTAINER - LWT (ES/006LW)

CONTAINER SPECIFICATIONS

| | |
|------------------------|---|
| <u>BASE</u> | 4mm mild steel plate (single plate) supported by |
| <u>BASE SUPPORTS</u> | Twin runners of RSC102mm x 51mm (4" x 2" channel) |
| <u>SIDES & END</u> | 3mm mild steel plate |
| <u>ROOF</u> | 3mm mild steel plate |
| <u>REINFORCEMENT</u> | RSC76mm x 38mm x 6.7kg/metre |
| <u>LIFTING LUGS</u> | 4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates |
| <u>TIPPING BARS</u> | 35mm mild steel tipping bar with FLT6mm pressed plate supports – TIPPING END ONLY |

DOOR SPECIFICATIONS

| | |
|--------------------|--|
| <u>TIPPING END</u> | 3mm mild steel side opening full width and full height double doors Reinforced with PSC76mm x 38mm formed from 3mm mild steel plate Doors are secured in the closed position using a 35mm locking shaft with 25mm thick profiled locking hooks Locking shafts held closed by secondary retaining bracket secured using a pin and chain assembly |
| <u>OTHER END</u> | 3mm full width double doors with FLT50mm x 5mm slam strip and RND10mm handles Doors are secured in the closed position using a spring bolt on top and bottom of doors And an antiluce fastener (to which a padlock may be fitted by customer) |

PAINTING SPECIFICATIONS

| | |
|----------------|---|
| <u>INSIDE</u> | Unpainted |
| <u>OUTSIDE</u> | One coat primer, two coats finishing enamel in colour of your choice. |



Showing REL type rear doors



USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD ENCLOSED SKIP PRICES

- (1) **ALL** plate seams fully welded – outside only / inside is stitched
- (2) **FULLY WELD** along top of top channels (to help prevent the ingress of water spoiling paint finish)
- (3) **SKIP LUGS** fitted through channels and side plate (fully welded both inside and outside)
- (8) **ALL SKIPS** of 8 CUYDS and above have backing plates welded behind skip lugs
- (9) **ALL SKIPS** of 8 CUYDS and over have both ends of tipping bar(s) capped in
- (4) **GJF ASSET** numbers welded on all containers for trace ability and security
- (7) **FACILITY** to weld on customer's asset numbers
- (8) **ALL STEEL** used is prime mild HR15 or 43A

| OVERALL INTERNAL DIMENSIONS | | |
|-----------------------------|----------------|-------------|
| LENGTH | WIDTH | HEIGHT |
| 11' 8" (3556mm) | 5' 9" (1753mm) | 6' (1830mm) |