

## SPECIFICATIONS: 40 CUYD OPEN HOOKLIFTCONTAINER (HL/010)

### CONTAINER BODY SPECIFICATIONS

|                          |  |
|--------------------------|--|
| <u>BASE</u>              | mild steel plate (2 pieces)  |
| <u>"A" FRAME</u>         | RSC 178mm x 76mm x 20.84kg/metre with 12mm reinforcing plates with Rnd65mm dia hook bar with deflector plate |
| <u>SIDES</u>             | mild steel plate - with 4 swages (folds)   |
| <u>HEADBOARD</u>         | mild steel plate reinforced with RHS150mm x 100mm x 5mm and RHS80mm x 80mm x 3.6mm                           |
| <u>VERTICAL CHANNELS</u> | PSC 100mm x75mm x 3mm (8 each side) – FULLY WELDED   |
| <u>TOP RAIL</u>          | RHS 80mm x 80mm x 3.6mm  |

### UNDERFRAME

|                      |   |
|----------------------|---|
| <u>MAIN FRAME</u>    | Twin runners of RSC 178mm x 76mm 20.84kg/metre with 65mm x 10mm wear strips and 5mm flitch plates |
| <u>FLOOR BEARERS</u> | 8 no. PSC100mm x 50mm formed from 5mm mild steel  |
| <u>ROLLERS</u>       | Twin rollers 229mm diameter x 229mm long with oil lite bearings                                   |

### DOOR ASSEMBLY SPECIFICATIONS

|                     |   |
|---------------------|---|
| <u>ALL DOORS</u>    | 4mm mild steel plate. ALL hinges are fitted with OIL LITE BEARINGS  |
| <u>BARN DOORS</u>   | Twin side opening double doors reinforced with PSC100mm x 50mm x 4mm<br>With primary and secondary locking mechanisms |
| <u>SINGLE DOOR</u>  | Reinforced with RHS 80mm x 80mm x 3.6mm   |
| <u>DOOR PILLARS</u> | RHS160mm x 80mm x 5mm   |

### PAINTING SPECIFICATIONS

|                |   |
|----------------|---|
| <u>INSIDE</u>  | One Coat primer only  |
| <u>OUTSIDE</u> | One coat primer, two coats finishing enamel in colour of your choice. |



SHOWING BARN DOOR OPTION

### USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD HOOKLIFT PRICES

#### STRENGTH AND SAFETY

- (1) **ALL PLATE** seams fully welded – both inside and outside
- (2) **9 UPRIGHTS** fully welded to side plates to increase strength of container
- (3) **5mm THICK** pressed channel floor bearers for extra floor strength
- (4) **PRIMARY AND SECONDARY** door locking facilities
- (5) **MAINTENANCE FREE** oil lite bearings fitted to both rollers and all hinges
- (6) **ALL HEADBOARDS** reinforced with RHS 150mm x 100mm x 5mm for extra rigity and strength (and RHS80mm x 80mm x 3.6mm on containers 30 cuyds and over
- (7) **DEFLECTOR PLATE** fitted to headboard
- (8) **ALL STEEL** used is prime mild steel (grades:HR15 and 43A)

#### EASE OF USAGE AND SECURITY

- (1) **CUSTOMER'S ASSET NUMBERS** or letters welded (or burnt) – at NO extra charge
- (2) **GJF ASSET** numbers welded on all containers for trace ability and security
- (3) **ROLLERS** removable and easily changed without any welding
- (4) **LADDER** welded on both sides at headboard end
- (5) **ROPE HOOKS** welded all around container

#### OVERALL INTERNAL DIMENSIONS

| LENGTH      | WIDTH         | HEIGHT      |
|-------------|---------------|-------------|
| 19'(5792mm) | 7'2" (2184mm) | 8' (2438mm) |