

## SPECIFICATIONS: 12 CUYD OPEN HOOKLIFTCONTAINER (HL/018) **16' ext**

### CONTAINER BODY SPECIFICATIONS

<u>BASE</u>	mild steel plate (2 pieces)
<u>"A" FRAME</u>	RSC 178mm x 76mm x 20.84kg/metre with 12mm reinforcing plates with Rnd65mm dia hook bar with deflector plate
<u>SIDES</u>	mild steel plate - with 1 swages (folds)
<u>HEADBOARD</u>	mild steel plate reinforced with RHS150mm x 100mm x 5mm
<u>VERTICAL CHANNELS</u>	PSC 100mm x75mm x 3mm (6 each side) – FULLY WELDED
<u>TOP RAIL</u>	RHS 80mm x 80mm x 3.6mm

### UNDERFRAME

<u>MAIN FRAME</u>	Twin runners of RSC 178mm x 76mm 20.84kg/metre with 65mm x 10mm wear strips and 5mm flitch plates
<u>FLOOR BEARERS</u>	6 no. PSC100mm x 50mm formed from 5mm mild steel
<u>ROLLERS</u>	Twin rollers 229mm diameter x 229mm long with oil lite bearings

### DOOR ASSEMBLY SPECIFICATIONS

<u>ALL DOORS</u>	4mm mild steel plate. ALL hinges are fitted with OIL LITE BEARINGS
<u>BARN DOORS</u>	Twin side opening double doors reinforced with PSC100mm x 50mm x 4mm With primary and secondary locking mechanisms
<u>SINGLE DOOR</u>	Reinforced with RHS 80mm x 80mm x 3.6mm
<u>DOOR PILLARS</u>	RHS160mm x 80mm x 5mm

### PAINTING SPECIFICATIONS

<u>INSIDE</u>	One Coat primer only
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



### USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD HL16 HOOKLIFT PRICES

#### STRENGTH AND SAFETY

- (1) **ALL PLATE** seams fully welded – both inside and outside
- (2) **6 UPRIGHTS** fully welded to side plates to increase strength of container
- (3) **5mm THICK** pressed channel floor bearers for extra floor strength
- (4) **PRIMARY AND SECONDARY** door locking facilities
- (5) **MAINTENANCE FREE** oil lite bearings fitted to both rollers and all hinges
- (6) **ALL HEADBOARDS** reinforced with RHS 150mm x 100mm x 5mm for extra rigity and strength
- (7) **DEFLECTOR PLATE** fitted to headboard
- (8) **ALL STEEL** used is prime mild steel (grades:HR15 and 43A)

#### EASE OF USAGE AND SECURITY

- (1) **CUSTOMER'S ASSET NUMBERS** or letters welded (or burnt) – at NO extra charge
- (2) **GJF ASSET** numbers welded on all containers for traceability and security
- (3) **ROLLERS** removable and easily changed without any welding
- (4) **LADDER** welded on both sides at headboard end
- (5) **ROPE HOOKS** welded all around container

<b>OVERALL INTERNAL DIMENSIONS</b>		
<b>LENGTH</b>	<b>WIDTH</b>	<b>HEIGHT</b>
15'(4572mm)	7'2" (2184mm)	3' (762mm)