

SPECIFICATIONS: 26 CUYD HOOKLIFT PAPERBANK (HL/060)

CONTAINER BODY SPECIFICATIONS

<u>BASE</u>	4mm mild steel plate (2 pieces)
<u>"A" FRAME</u>	RSC 178mm x 76mm x 20.84kg/metre with 12mm reinforcing plates with Rnd65mm dia hook bar with deflector plate
<u>SIDES</u>	3mm mild steel plate – not swaged
<u>APPERTURES</u>	5 letterboxes each side of container (794mm Long)
<u>HEADBOARD</u>	4mm mild steel plate reinforced with RHS150mm x 100mm x 5mm
<u>ROOF</u>	3mm mild steel plate reinforced with RHS40mm x 40mm x 2.5mm

UNDERFRAME

<u>MAIN FRAME</u>	Twin runners of RSC 178mm x 76mm 20.84kg/metre with 65mm x 10mm wear strips and 5mm flitch plates
<u>FLOOR BEARERS</u>	8 no. PSC100mm x 50mm formed from 5mm mild steel
<u>ROLLERS</u>	Twin rollers 229mm diameter x 229mm long with oil lite bearings

DOOR ASSEMBLY SPECIFICATIONS

<u>ALL DOORS</u>	4mm mild steel plate. ALL hinges are fitted with OIL LITE BEARINGS
<u>SINGLE DOOR</u>	Reinforced with RHS 80mm x 80mm x 3.6mm
<u>DOOR PILLARS</u>	RHS160mm x 80mm x 5mm

PAINTING SPECIFICATIONS

<u>INSIDE</u>	Unpainted
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD HOOKLIFT PRICES

STRENGTH AND SAFETY

- (1) **ALL PLATE** seams fully welded – both inside and outside
- (3) **5mm THICK** pressed channel floor bearers for extra floor strength
- (3) **5mm THICK** pressed channel floor bearers for extra floor strength
- (4) **PRIMARY AND SECONDARY** door locking facilities
- (5) **MAINTENANCE FREE** oil lite bearings fitted to both rollers and all hinges
- (6) **ALL HEADBOARDS** reinforced with RHS 150mm x 100mm x 5mm for extra rigity and
- (7) **DEFLECTOR PLATE** fitted to headboard
- (8) **ALL STEEL** used is prime mild steel (grades:HR15 and 43A)

EASE OF USAGE AND SECURITY

- (1) **GJF ASSET** numbers welded on all containers for traceability and security
- (2) **ROLLERS** removable and easily changed without any welding

OVERALL INTERNAL DIMENSIONS

LENGTH	WIDTH	HEIGHT
19'(5792mm)	7'2" (2184mm)	5' 3" (1600mm)
LOADING HEIGHT FROM FLOOR 5'6" (1695mm)		