



CHASE LINK
 LICHFIELD ROAD
 BROWNHILLS, WALSALL
 WEST MIDLANDS
 WS8 6LA

Telephone: 01543 360777
 Facsimile: 01543 360977

SPECIFICATIONS: 20 CUYD OPEN MINIHOOKLIFT CONTAINER

(MH/013)

CONTAINER BODY SPECIFICATIONS

<u>BASE</u>	3mm mild steel plate (2 pieces)
<u>"A" FRAME</u>	RSC 127mm x 64mm x 14.9 kg/metre with reinforcing plates with 35mm dia. bar
<u>SIDES</u>	3mm mild steel plate -with 3 swages (folds)
<u>HEADBOARD</u>	3mm mild steel plate reinforced with RHS 150mm x 100mm x 5mm
<u>VERTICAL CHANNELS</u>	RHS 80mm x 40mm x 3mm) – FULLY WELDED
<u>TOP RAIL</u>	RHS 80mm x 40mm x 3mm

UNDERFRAME

<u>MAIN FRAME</u>	RSC 127mm x 64mm x 14.90 kg/metre twin runners with 4mm flitch plates
<u>FLOOR BEARERS</u>	4 no. RHS80mm x 40mm x 3.6mm and 4 no. RHS40mm x 40mm x 2.5
<u>ROLLERS</u>	Twin rollers 114mm diameter x 250mm long

DOOR ASSEMBLY SPECIFICATIONS

<u>ALL DOORS</u>	3mm mild steel plate and 2" x 2" x 4mm thick welded steel mesh
<u>BARN DOORS</u>	Twin side opening double doors reinforced with PSC76mm x 38mm formed from Formed from 3mm mild steel
<u>DOOR PILLARS</u>	RHS100mm x 50mm x 5mm

PAINTING SPECIFICATIONS

<u>INSIDE</u>	One Coat primer only
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD MINI HOOKLIFT PRICES

- (1) **ALL** plate seams fully welded – both inside and outside
- (2) **FULLY WELD** along top of top channels (to help prevent the ingress of water spoiling paint finish)
- (3) **GJF ASSET** numbers welded on all containers for trace ability and security
- (4) **FACILITY** to weld on customer's asset numbers (or burn in letters)
- (5) **ALL STEEL** used is prime mild HR15 or 43A

OVERALL INTERNAL DIMENSIONS		
LENGTH 12' (3660mm)	WIDTH 7' 7 1/4" 2316mm)	HEIGHT 6' 6" (1980mm)