



CHASE LINK
 LICHFIELD ROAD
 BROWNHILLS, WALSALL
 WEST MIDLANDS
 WS8 6LA

Telephone: 01543 360777
 Facsimile: 01543 360977

SPECIFICATIONS: 7 CUYD DROP DOOR SKIP (OS/010)

CONTAINER SPECIFICATIONS

<u>BASE</u>	6mm mild steel plate
<u>SIDES & ENDS</u>	4mm mild steel
<u>REINFORCEMENT</u>	RSC76mm x 38mm x 6.7kg/metre – SINGLE RAIL
<u>LIFTING LUGS</u>	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BAR</u>	35mm mild steel tipping bar with FLT6mm pressed plate supports – ONE END ONLY

DOOR SPECIFICATIONS

<u>GUSSETING</u>	Substantial 3mm mild steel gusseting each side and below door opening RSC 76mm x 38mm reinforcement on inside of skip below door
<u>DOOR DETAILS</u>	Lift up and open 3mm mild steel door reinforced with RSC 76 x 38mm Door pivots on RSC76mm x 38mm and is fitted with secondary locking facility

PAINTING SPECIFICATIONS

<u>INSIDE</u>	One Coat primer only
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD OPEN SKIP PRICES (3 CUYD & ABOVE)

- (1) **ALL** plate seams fully welded – both inside and outside
- (2) **FULLY WELD** along top of top channels (to help prevent the ingress of water spoiling paint finish)
- (3) **FULLY GUSSETED** (with 3mm mild steel plate) all around door surround (to help prevent skip spreading when door is open)
- (4) **DOOR REINFORCED** with RSC76mm x 38mm x 6.7kg/metre for extra strength
- (5) **LIFT UP AND OPEN** door to prevent accidental opening
- (6) **SKIP LUGS** fitted through channels and side plate (fully welded both inside and outside)
- (7) **GJF ASSET** numbers welded on all containers for trace ability and security
- (8) **FACILITY** to weld on customer's asset numbers (or burn in letters)
- (9) **ALL STEEL** used is prime mild steel (grades:HR15 and 43A)

OVERALL INTERNAL DIMENSIONS

LENGTH	WIDTH	HEIGHT
9' 7" (2921mm)	5' 9" (1759mm)	4' 1 1/4" (1250mm)