



CHASE LINK  
LICHFIELD ROAD  
BROWNHILLS, WALSALL  
WEST MIDLANDS  
WS8 6LA

Telephone: 01543 360777  
Facsimile: 01543 360977

## **SPECIFICATIONS: 8 CUYD ENCLOSED REAR END LOADER** ***With PLASTIC LIDS (REL/002PL)***

### **CONTAINER SPECIFICATIONS**

<u>BASE</u>	4mm mild steel plate (single plate) supported by
<u>BASE SUPPORTS</u>	Twin runners of RSC102mm x 51mm (4" x 2" channel)
<u>SIDES &amp; ENDS, ROOF</u>	3mm mild steel plate
<u>REINFORMENT</u>	RSC76mm x 38mm x 6.7kg/metre
<u>LIFTING LUGS</u>	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	35mm mild steel tipping bar with FLT6mm pressed plate supports – TIPPING END ONLY

### **DOOR SPECIFICATIONS**

<u>TIPPING END</u>	<b>GENUINE DURAFLEX</b> polyurethane double doors. Supplied with a detachable handle to ease opening
<u>REAR</u>	3mm mild steel full-width side opening doors

### **LIFTING HEAD SPECIFICATIONS**

<u>MAIN MEMBER</u>	RHS120mm x 120mm with TUBE 76mm O/D lifting ( <i>pins are not included as standard</i> )
<u>STRENGTHENERS</u>	RSC76mm x 38mm x 6.7kg/metre horizontal and vertical stiffeners

### **PAINTING SPECIFICATIONS**

<u>INSIDE</u>	Unpainted
<u>OUTSIDE</u>	One coat primer, two coats finishing enamel in colour of your choice.



### **USEFUL OPTIONS INCLUDED IN ALL GJF'S STANDARD ENCLOSED R.E.L. PRICES**

- (1) **ALL** plate seams fully welded – outside only / inside is stitched
- (2) **FULLY WELD** along top of top channels (to help prevent the ingress of water spoiling paint finish)
- (3) **SKIP LUGS** fitted through channels and side plate (fully welded both inside and outside)
- (4) **RSC RUNNERS** fitted underneath base plate to increase life of containers
- (5) **STABILISERS** of 3mm mild steel plate fitted for increased stability
- (5) **ALL RELS** of 8 CUYDS and above have backing plates welded behind skip lugs
- (6) **ALL RELS** of 8 CUYDS and over have both ends of tipping bar(s) capped in
- (7) **GJF ASSET** numbers welded on all containers for trace ability and security
- (8) **FACILITY** to weld on customer's asset numbers (or burn in letters)
- (9) **ALL STEEL** used is prime mild HR15 or 43A

<b>OVERALL INTERNAL DIMENSIONS</b>		
<b>LENGTH</b>	<b>WIDTH</b>	<b>HEIGHT</b>
<b>11' 3/4" (3378mm)</b>	<b>5' 9" (1753mm)</b>	<b>5' (1524mm)</b>